HyPanel

Datasheet

New hassle-free smart control panel for your home

The akubela HyPanel, a smart control panel with an Android 10 operating system. The ALL IN ONE design integrates smart intercom, ZigBee gateway and home automation, and it is compatible with plentiful ecosystem. Multi-modal interaction can be easily used by the whole family, offering the excellent smart home experience.

At a Glance

- Excellent performance with Android 10 system
- 4" multi-touch screen with energy saving mode
- 1 gang dimmer, replace conventional switch
- Smart intercom, ZigBee gateway, home automation ALL IN ONE
- Kinds of sensors built-in
- EU standard flush mounted box

Basic Information

- Model Number: PS51-D1-EU
- Power Supply: 180 ~ 260VAC, 50Hz
- Output: 1 gang, 300W total;
 - 300W/gang for resistive;
 - 150W/gang for LED/CFL;
 - Wire Range: 0.5 ~ 2.5mm² (24 ~ 12AWG)
- Power Meter: Supported
- Operation System: Android 10
- RAM/ROM: 1GB/8GB
- Wi-Fi: IEEE802.11 b/g/n, @2.4GHz/5GHz
- Bluetooth: Bluetooth 4.2
- Ethernet Port: 1×RJ45, 10/100Mbps adaptive
- ZigBee: ZigBee 3.0
- ZigBee Sub-Device Limit: 128

- Microphone: Dual microphones, -42dBV
- Speaker: Single speaker, $8\Omega/1.5W$

Appearance

- Material: V0 fireproof PC
- Screen: 4" multi-touch screen
- Screen Resolution: 480×480 pixels
- Screen Brightness: 210 cd/m2

Sensors Built In

- Proximity Sensor: 30 ~ 60cm
- Light Sensor: Low-level lux detection
- Temperature Sensor: ±1°C, range: -10°C ~ 55°C
- Humidity Sensor: ±5%, range: 10% ~ 90%RH, without condensation

📿 akubela

10/F, No.56 Guanri Road, Software Park II , Xiamen 361009, China Tel: +86-592-2133061 Ext: 7694 Fax: +86-592-2133061 Email: sales@akuvox.com Web: www.akubela.com




HyPanel

Datasheet


Working Environment

- Environment: For indoor use only
- Working Humidity: 10% ~ 90%RH, without condensation
- Working Temperature: -10°C \sim 55°C
- Storage Temperature: -20°C \sim 65°C
- IP Rating: IP20

Product Dimension Diagram (mm)





86.0



88.0

1 FRONT VIEW






Installation

• Installation: Wall flush mounting

• Wiring Way: L- + N- wire required

• Flush Mounted Module: EU/UK standard



(4) BACK VIEW

🕜 akubela

10/F, No.56 Guanri Road, Software Park III , Xiamen 361009, China Tel: +86-592-2133061 Ext: 7694 Fax: +86-592-2133061 Email: sales@akuvox.com Web: www.akubela.com