HyPanel Datasheet

### New hassle-free smart control panel for your home

The akubela HyPanel Heating version, a smart heating thermostat control panel with an Android 10 operating system. The ALL IN ONE design integrates smart intercom, ZigBee gateway, Thermostat, and home automation, and it is compatible with plentiful ecosystem. Multi-modal interaction can be easily used by the whole family, offering the excellent smart home experience.

#### At a Glance

- Excellent performance with Android 10 system
- 4" multi-touch screen with energy saving mode
- Support heating thermostat control
- Smart intercom, ZigBee gateway, home automation ALL IN ONE
- Kinds of sensors built-in
- EU standard flush mounted box



### **Basic Information**

- Model Number: PS51-HEATING-EU
- Power Supply: 100 ~ 250VAC, 50/60Hz
- Built-in Relay Capacity: 20A
- Maximum Resistive Load: 16A (4000W @ 250VAC)

Wire Range:  $1.5 \sim 2.5 \text{mm}^2$  ( $16 \sim 12 \text{AWG}$ )

- Power Meter: Supported
- Operation System: Android 10
- RAM/ROM: 1GB/8GB
- Wi-Fi: IEEE802.11 b/g/n, @2.4GHz/5GHz
- Bluetooth: Bluetooth 4.2
- ZigBee: ZigBee 3.0
- ZigBee Sub-Device Limit: 128
- Bell In: Supported

- NTC Measurement Range: -30°C ~ 80°C
  - Accuracy: ±0.5°C
- Microphone: Dual microphones, -42dBV
- Speaker: Single speaker,  $8\Omega/1.5W$

## **Appearance**

- Material: V0 fireproof PC
- Screen: 4" multi-touch screen
- Screen Resolution: 480×480 pixels
- Screen Brightness: 210 cd/m²

#### Sensors Built In

- Proximity Sensor: 30 ~ 60cm
- Light Sensor: Low-level lux detection
- Temperature Sensor: ±1°C, range: -10°C ~ 55°C
- Humidity Sensor: ±5%, range: 10% ~ 90%RH,
  without condensation



HyPanel Datasheet

# Working Environment

• Environment: For indoor use only


 Working Humidity: 10% ~ 90%RH, without condensation


• Working Temperature:  $-10^{\circ}$ C  $\sim 45^{\circ}$ C


• Storage Temperature: -20°C ~ 65°C


• IP Rating: IP20

# Product Dimension Diagram (mm)









## Installation

• Installation: Wall flush mounting

• Flush Mounted Module: EU/UK standard

• Wiring Way: L- + N- wire required

